

Easy-Lead R Textured & Smooth

Datasheet

Issue Date: June 2019

Description

BBA approved Easy Lead R and Easy Lead R Smooth are aluminium based, high performance, low cost flashing products. They are used as a replacement for traditional lead in flat and pitched roof applications. Made of sheet aluminium with a protective anti-corrosion coating and a high performance butyl adhesive on the underside. Installation is simple, with no special tools required it can be cut with a knife or scissors. EasyLead R has a unique corrugated pattern so it is easy to form and to adapt to various surfaces; this malleability ensures the permanent water tightness of the product and an attractive appearance every time. EasyLead R Smooth has the same benefits and characteristics of EasyLead R, only with a smooth finish thus effectively mimicking the appearance of traditional lead. EasyLead R provides a permanent bond to brickwork, roof tiles and most popular construction materials.

Key features to EasyLead R and EasyLead R Smooth

- Zero re-sale value - theft and vandalism are eliminated
- Cost effective alternative to traditional lead
- Waterproof
- Durable
- Malleable
- Easy to install
- Easily cut
- Easily repaired
- Extremely lightweight

Typical application

- Abutments
- Chimneys
- Dormers
- Saddles
- Soakers
- Stepped
- Valleys
- Windows and rooflights
- Valleys and gutters

Installation

Easily installed using a knife or scissors to cut. Can be installed and worked in any direction using a mallet, roller or by hand. Determine the final installation of EasyLead R or EasyLead R Smooth maintaining the release film until achieved, once satisfied remove the release film and press the material to the brickwork or applicable surface. Joints should have a minimum overlap of 100mm. To achieve permanent adhesion, the building material surface has to be clean and dry. A bituminous primer is recommended for unstable material surfaces.



Product Code	Description	Pallet Qty
EASYLEADR1505	EASY LEAD R TEXTURED 150MM X 5M ROLL	192
EASYLEADR3005	EASY LEAD R TEXTURED 300MM X 5M ROLL	96
EASYLEADR4505	EASY LEAD R TEXTURED 450MM X 5M ROLL	72
EASYLEADR6005	EASY LEAD R TEXTURED 600MM X 5M ROLL	48
EASYLEADR1505SMT	EASY LEAD R SMOOTH 150MM X 5M ROLL	192
EASYLEADR3005SMT	EASY LEAD R SMOOTH 300MM X 5M ROLL	96
EASYLEADR4505SMT	EASY LEAD R SMOOTH 450MM X 5M ROLL	72
EASYLEADR6005SMT	EASY LEAD R SMOOTH 600MM X 5M ROLL	48

Technical Data

- Colour: Grey
- Surface finish: Corrugated/smooth
- Temperature resistance: -40°C / +90°C
- Minimum working temp: +5°C
- Life expectancy: Minimum 20 yrs
- Resistant against corrosion and UV degradation: Yes

Product Data

	150	300	450	600
Roll width/mm	150	300	450	600
Roll length/mtrs	5mtr	5mtr	5mtr	5mtr
Roll weight/kilos	1.5	3	4.5	6

